



HYDRAULIC & INDUSTRIAL HOSE




TECH2SNK | **EXCEEDS SAE100R16S**



- Tube:** Oil resistant synthetic rubber
- Reinforcement:** Two braid of high tensile steel wire
- Cover:** Diamond Tuff Cover, 16 times more abrasion resistant than ISO 6945 standards. Oil and weather resistant black synthetic rubber smooth cover
- Application:** High pressure hydraulic lines

HOSE SIZE I.D.			HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MIN. BEND RADIUS	WEIGHT	COMPATIBLE FITTINGS	
SIZE	INCH	MM	INCH	MM	PSI	BAR	PSI	BAR	MM	LBS/FT		
TECH2SNK-04	1/4"	6.4	0.52	13.1	6530	450	26100	1800	45	0.18	A	ST34
TECH2SNK-06	3/8"	9.5	0.67	17.1	5590	385	22230	1540	65	0.26	A	ST34
TECH2SNK-08	1/2"	12.5	0.80	20.3	5010	345	20010	1380	80	0.36	A	ST34
TECH2SNK-10	5/8"	15.8	0.97	24.7	4640	320	18560	1280	90	0.48	A	ST34
TECH2SNK-12	3/4"	19.0	1.09	27.7	4350	300	17400	1200	120	0.58	A	ST34
TECH2SNK-16	1"	25.4	1.41	35.8	3270	225	13050	900	160	0.88	A	ST34

HOSE

-  **HYDRAULICS OILS:** FROM -40°F / +212°F (-40°C / +100°C)
- WATER GLYCOL HYDRAULIC FLUIDS:** FROM -40°F / +158°F (-40°C / +70°C)
- WATER:** FROM +32°F / +158°F (0°C / +70°C)
- AIR:** UP TO +158°F (UP TO +70°C) All wire braid hose covers should be pin-pricked to use air above 145 psi or (10 Bar)